ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INFORMATION AND A	IPC. Bannockt	ourn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declara he declaration	ion of the s encompasse	ubstances es all lowe	within the n r level mater	nanufacture rials for whi	er listed item ich the manu	. Note: if ifacturer	the item is an as has engineering	sembly with lowe responsibility.
				Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
Supplier Information														
Company name* C			Company unique ID			Unique ID Authority					Response Date*			
onsemi											2023-06-08			
Contact Name Title - Conta Product-Env-Stewards Product Envi			ntact nviro Compliance			Phone - Contact* NA					Email - Contact* Product-Env-Stewards@onsemi.com			
Authorized Representative* Title -			itle - Representative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item	Number	Mfr Item Name			Effective Dat	ive Date Version Manufacturing Site		ng Site	Wei	ght*	UOM	Unit Type	
	UC3843	UC3843BDR2G ANA SMPS PWI		M CONTROLLI	ER	2023-06-08		]	PH1		122	04	mg	Each
Manufacturing Proccess Information	ation						-	·						
Terminal Plating / Grid Array M	Il Plating / Grid Array Material Terminal Base Alloy			J-STD-020 MSI	ISL Rating Peak Process Body Temperature Max Time at					ne at Peak T	ak Temperature Number of Reflow Cycles			
Matte Tin (Sn) - annealed CU Alloy				1		260		С	30		seconds	3		
omments														
vel 1 - maximum time at peak temperat	ure during so	dering is 10-3	0 seconds											
or more information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the				
Supplier Digital Signature Ra	stislav Drska	Le							

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.98	mg	Supplier	Silicon (Si)	7440-21-3		0.98	mg
Die Attach	4.44	mg		Epoxy resin	proprietary data		0.444	mg
			Supplier	Ethylene dimethacrylate	97-90-5		0.222	mg
			Supplier	Silver (Ag)	7440-22-4		3.552	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.222	mg
Lead Frame	69.62	mg	Supplier	Silver (Ag)	7440-22-4		0.7658	mg
			Supplier	Zinc (Zn)	7440-66-6		0.1392	mg
			Supplier	Iron (Fe)	7439-89-6		1.8101	mg
			Supplier	Copper (Cu)	7440-50-8		66.9048	mg
Mold Compound-Black	43.43	mg		Epoxy resin	proprietary data		2.1715	mg
			Supplier	Phenolic Resin	Proprietary Data		2.1715	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.8686	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2172	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		38.0013	mg
Plating	3.27	mg	Supplier	Tin (Sn)	7440-31-5		3.27	mg
Wire Bond - Cu	0.3	mg	Supplier	Copper (Cu)	7440-50-8		0.3	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).